



A WIDE RANGE OF VISCOSITIES
to suit all equipment and applications

Mobil™

Mobil™ lubricants: make the right choice to ensure long life of your refrigeration plant

Oil is a key element in your installation. It must be selected with care to **ensure that your compressor runs smoothly and be compatible with the refrigerant** used in the installation.

Thanks to our long-standing partnership with Mobil™, producer of industrial lubricants and oils for refrigeration compressors, and with our experience, we have created a refrigerant/oil correlation table to simplify your choice.

Make life easier for yourself and put your trust in the expertise of Mobil™ and Climalife:

Refrigerant type	Compressor type	Evaporating t°C	Mobil™ Solutions
HFO			
Solstice® ze (R-1234ze)	Piston	❄ -20°C to +10°C	Mobil SHC Gargoyl [™] 32 Mobil EAL Arctic [™] 68 & 100 Mobil EAL Arctic [™] 170 & 220
	Centrifugal		
	Screw		
Solstice® yf (R-1234yf)	Piston	❄ -30°C to -10°C	Mobil EAL Arctic [™] 22CC & Mobil SHC Gargoyl [™] 32
	Screw		Mobil EAL Arctic [™] 100 &170
	Centrifugal		Mobil EAL Arctic [™] 68 & 100
HFO BLENDS			
Solstice® L40X (R-455A)	Piston	❄ -50°C to -30°C	Mobil SHC Gargoyl [™] 32
	Screw		Mobil EAL Arctic [™] 100 & 170
	Centrifugal		Mobil EAL Arctic [™] 68 & 100
Solstice® N40 (R-448A) Solstice® 449A (R-449A)	Piston	❄ -40°C to 0°C	Mobil SHC Gargoyl [™] 32 & Mobil EAL Arctic [™] 22CC
	Screw		Mobil EAL Arctic [™] 100 & 170
	Centrifugal		Mobil EAL Arctic [™] 68 & 100
Solstice® 513A (R-513A)	Piston	❄ -30°C to -10°C	Mobil SHC Gargoyl [™] 32 & Mobil EAL Arctic [™] 22CC
	Screw		Mobil EAL Arctic [™] 100 & 170
	Centrifugal		Mobil EAL Arctic [™] 68 & 100
Solstice® N71 (R-471A)	New refrigerant Group A1 with a GWP <150 Testing in progress Will be approved very soon		
AMMONIA			
R-717	Piston & Screw	❄ -50°C to +10°C	Mobil Gargoyl [™] SHC [™] 226E Mobil Gargoyl [™] Arctic SHC [™] NH 68
		❄ -40°C to +10°C	Mobil Gargoyl [™] SHC [™] 226E Mobil Gargoyl [™] Arctic SHC [™] NH 68 Mobil Gargoyl [™] Arctic 68 NH
		❄ -30°C to +10°C	Mobil Gargoyl [™] SHC [™] 226E Mobil Gargoyl [™] Arctic SHC [™] NH 68 Mobil Gargoyl [™] Arctic 68 NH Mobil Gargoyl [™] Arctic [™] Oil 300
	Centrifugal	❄ -50°C to +10°C	Mobil Gargoyl [™] SHC [™] 226E Mobil Gargoyl [™] Arctic SHC [™] NH 68
		❄ -40°C to +10°C	Mobil Gargoyl [™] SHC [™] 226E Mobil Gargoyl [™] Arctic SHC [™] NH 68 Mobil Gargoyl [™] Arctic 68 NH
		❄ -30°C to +10°C	Mobil Gargoyl [™] SHC [™] 226E Mobil Gargoyl [™] Arctic SHC [™] NH 68 Mobil Gargoyl [™] Arctic 68 NH Mobil Gargoyl [™] Arctic [™] Oil 300
MISCIBLE CO ₂			
R-744	Piston	❄ -55°C to -10°C	Mobil SHC Gargoyl [™] 80 POE
PROPANE			
R-290	Screw & Piston (non miscible)	❄ -30°C to +20°C	Mobil Glygoyl [™] 22
	Screw & Piston & Centrifugal (miscible)		Mobil Gargoyl [™] Arctic SHC [™] 200 series Mobil Gargoyl [™] Arctic [™] Oil 300

The benefits of Mobil™ oils:



Superior quality
Very high performance



High miscibility
Greater system efficiency



Thermal stability
Long service life